

# BUILDING PRODUCT INFORMATION SHEET

CLASS 1 – December 2025

**Product Name:** bbi SupaForm F17 Formwork Plywood

## Product Description and Intended Use:

SupaForm F17 Formwork Plywood is a product intended for use general uses in the concrete forming industry for residential or commercial projects.

SupaForm formwork plywood is a wood veneer-based product, manufactured in accordance with AS6669:2016, which gives the assurance of the structural integrity that this product is designed for use in Australia and New Zealand.

SupaForm is available in the nominal 17mm thickness, with a film face applied to the C face grade surface veneers, that is F17 stress graded and is available untreated as standard. The SupaForm formwork plywood is assembled using the wood species of Eucalyptus, with the assembly of ply being 17-9-11.

## Product Identifier:

SupaForm F17 plywood can be identified by the markings on the sheets. The sheets are marked in accordance with AS6669:2016. This includes the country of origin and stress grading.



**Place of Manufacture:** Overseas

**Legal and Trading Name of Importer:** bbi Wood Products Ltd

**New Zealand Business Number (NZBN):** 9429033930442

**Address for Service:**

27 Poporo Way, Longlands,  
Hastings,  
New Zealand

**Website:** [www.bbi.net.nz](http://www.bbi.net.nz)

**Email Address:** [sales@bbi.net.nz](mailto:sales@bbi.net.nz)

**Phone Number:** 0800 224 759

## Relevant New Zealand Building Code Clauses:

- Clause B1 Structure: Performance: B1.3.1, B1.3.2, B1.3.3(a,b,c,f,h,j,q), B1.3.4(a,c,d,e)
- Clause B2 Durability Performance: B2.3.1(c)
- Clause F2 Hazardous Building Materials Performance: F2.3.1

## Statement on how the building product is expected to contribute to compliance:

SupaForm formwork plywood is intended for formwork applications for residential or commercial projects. SupaForm plywood has been manufactured in accordance with AS6669:2016 and assists in meeting the following provisions of the New Zealand Building Code:

### **Clause B1 Structure: Performance B1.3.1, B1.3.2, B1.3.3, B1.3.4:**

SupaForm structural form work plywood is made in a factory that is certified by an independent certification organization Shanghai Hongjun Technology Co. Limited as being manufactured in accordance with the Australian Standard, AS 6669 Form Work Plywood.

### **Clause B2 Durability: Performance B2.3.1:**

SupaForm plywood is manufactured to adhere with the requirements of the NZBC Clause B2 Durability. When the product is specified and used in accordance with good design and construction building practices, it will form part of the Acceptable Solution contributing to the requirements of the NZBC (B2/AS1).

### **Clause F2 Hazardous Building Materials: Performance F2.3.1:**

SupaForm plywood meets the requirements and will not present a hazard to people.

PremForm formwork plywood product, specified in accordance with New Zealand Building Code (NZBC) Clause B1/VM1 (B1 Structure Verification Method), B1/AS1 (B1 Structure Acceptable Solutions), NZS3603 Timber Structures Standard or NZS AS 1720.1:2022 Timber structures – Part 1: Design methods can be utilised for use as a structural formwork plywood panel within structural designs when specified by suitably qualified professionals and engineers. The installation and detailing of the PremForm plywood should be installed in accordance with the specifications and details as provided by the design professionals and engineers.

Durability is determined by the care and handling of PremForm plywood that should be detailed and specified by the suitably qualified design professionals and engineers to contribute to the requirements for a timber-based wood veneer product of the NZBC Durability Clause B2 (B2 Durability).

SupaForm plywood will continue to contribute to the relevant performance requirements of the New Zealand Building Code and other statutory time frames as specified by the designer or specifier of the project provided that the specific design parameters of the project are met and satisfied accordingly.

### **Limitations on the use of the building product:**

- SupaForm when cut, edges should be resealed to prevent moisture wicking.
- Appropriate handling and care should be taken to avoid mechanical damage to the formwork plywood, as this may affect the final product and formwork.
- The use of PremForm outside the intended application of formwork will be subject to specific design by the specifier of the project.

### **Design requirements that would support the appropriate use of the building product:**

SupaForm panels can be specified as a formwork substrate as part of a specific design.

The design requirements that would support the appropriate use of the SupaForm plywood panels would be subject to the detailing and specifications by the specifier of the project. It is the specifiers responsibility to ensure the correct design requirements and details are provided.



### Installation requirements:

SupaForm must be installed with good building practice, robust construction methodology and sound design principles by the engineer or suitably qualified design professional.

For specific installation guidance refer to your project lead for further specification and project specific detailing.

### Maintenance requirements:

SupaForm formwork plywood does not typically require maintenance. Where there are circumstances, the product is to be reused, care in handling should be considered prior to installation.

Refer to the FormPly Care & Handling Information Bulletin for further information on the reuse of the product and general guidance for form work plywood.

### Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

Yes  No

**Date: 15 December 2025**